



DIMENSIONS :

125L x 33H x 70W (mm)

FEATURES :

- 1.Passwords (3-12 digits) could be set by users
- 2.Maximum 80 users capacity.
- 3.Duress code installation.
- 4.3 continuity of wrong passwords entered may temporarily shut down the reader for 20 seconds and alarm will be activated.
- 5.6-digit user password could be set by user
- 6.Polycarbonate fireproof material for casing , white or dark-gray.

SPECIFICATIONS :

- Passwords (3-12 digits) could be set by users. Maximum 80 users capacity.
- Duress code installation. If being held as hostage specific secret code can be entered and help signal will be dispatched.
- Tamper switch. Alarm will be activated when machine is being tampered with force.
- Door opening could be set as normal or temporary states. When temporary state is set, user could set door opening time form 1-99 seconds. When normal state is set, all security system is being turned off.
- 6-digit user password could be set by user. User could add on delete other passwords as well.
- Three door opening methods: password door opening, system password opening, push button door opening, for the convenience of security guard.
- 3 continuity of wrong passwords entered may temporarily shut down the reader for 20 seconds and alarm will be activated.
- 0~65oC,85%Rhm_o

PT. Citra Amantosa Sejati. Kebon Jeruk Baru, Ruko blok A-15, Jakarta 11530

Phone : 021-5308435, 5323403, 5350058 Fax. : 021-5308434

E-mail : info@cas.co.id Web-site : <http://www.cas.co.id>